



	CONVISION CC-6337-G	CONVISION CC-6400-G	CONVISION CC-6602-B	CONVISION CC-6604DIR-B
Description	Fast PTZ dome camera with 37x optical zoom and wide dynamic range (WDR).	Fast PTZ dome camera with 10x optical zoom.	Fixed camera with digital wide dynamic range (WDR) and IR LEDs for 25m viewable distance.	Dome camera with wide dynamic range (WDR) and IR LEDs for 15m viewable distance.
Camera				
Picture sensor	1/4" Sony CCD	1/4" Sony CCD	1/3" Pixim CMOS	1/3" Pixim CMOS
Lens	3.5 - 129.5 mm F/1.6-3.9	3.8 - 38 mm F/1.8-2.8	2.8 - 10 mm F/1.2	2.8 - 10 mm F/1.2
Angle of view	54° - 1.6°	51° - 5.4°	81° - 27°	81° - 27°
Min. illumination (b/w / color)	0.4 / 0.02 Lux at F=1.6	0.4 / 0.02 Lux at F=1.8	0 Lux	0 Lux
IR-LEDs for optimized night operation	no	no	yes (25m viewable distance)	yes (15m viewable distance)
Day/night with IR cut filter	yes	yes	yes	yes
Pan / Tilt / Zoom (PTZ)	360° / 95° / 37x	360° / 95° / 10x	no	no
On screen display OSD	yes	yes	yes	yes
Video / Audio				
Video compression	H.264	H.264	H.264 (multistreaming)	H.264 (multistreaming)
Pixels	720 x 576 (D1)	720 x 576 (D1)	720 x 576 (D1)	720 x 576 (D1)
White balance	manual, automatically	manual, automatically	manual, automatically	manual, automatically
Privacy zone	8	8	12	12
Noise reduction (DNR)	yes	yes	yes	yes
Wide dynamic range (WDR)	yes	no	yes	yes
Sense Up	yes	yes	yes	yes
Motion detection	yes (414 zones)	yes (414 zones)	yes (414 zones)	yes (414 zones)
Audio input/output	2 way (Line in / Line out)	2 way (Line in / Line out)	no	2 way (Line in / Line out)
General				
Outdoor use	yes	yes	yes	yes
Degree of protection/Operating temperature	IP67 / -30 to +50 °C	IP66 / -30 to +50 °C	IP66 / -10 to +50 °C	IP66 / -10 to +50 °C
Additional features	vandalism protected	vandalism protected	vandalism protected	vandalism protected
Power consumption	12 V DC / 3 A	12 V DC / 3 A	12 V DC / 850 mA or PoE	12 V DC / 800 mA or PoE
Dimensions (HxWxD)	260 x 185 x 293 mm	237 x 158 x 273 mm	127 x 90 x 222 mm	148 x 148 x 128 mm
Weight	4 kg	3 kg	1.1 kg	1.1 kg
Color of housing	white	white	black	white



	CONVISION CC-6601-B	CONVISION CC-6605DIR-B
Description	Fixed camera with wide dynamic range (WDR) and CS-mount.	Dome camera with wide dynamic range (WDR) and IR LEDs for 15m viewable distance.
Camera		
Picture sensor	1/3" Pixim CMOS	1/3" Pixim CMOS
Lens	---	2.8 - 10 mm F/1.2
Angle of view	---	81° - 27°
Min. illumination (b/w / color)	0.1 / 0.01 Lux at F=1.0	0 Lux
IR-LEDs for optimized night operation	no	yes (15m viewable distance)
Day/night with IR cut filter	yes	yes
Pan / Tilt / Zoom (PTZ)	no	no
On screen display OSD	yes	yes
Video / Audio		
Video compression	H.264 (multistreaming)	H.264 (multistreaming)
Pixels	720 x 576 (D1)	720 x 576 (D1)
White balance	manual, automatically	manual, automatically
Privacy zones	12	12
Noise reduction (DNR)	yes	yes
Wide dynamic range (WDR)	yes	yes
Sense Up	yes	yes
Motion detection	yes (414 zones)	yes (414 zones)
Audio input/output	2 way (Line in / Line out)	2 way (Line in / Line out)
General		
Outdoor use	no	no
Degree of protection/Operating temperature	IP50 / -10 to +50°C	IP50 / -10 to +50 °C
Additional features		
Power consumption	12 V DC / 650 mA or PoE	12 V DC / 800 mA or PoE
Dimensions (HxWxD)	65 x 64 x 117 mm	148 x 148 x 128 mm
Weight	0.3 kg	1.1 kg
Color of housing	silver	white

PCS Systemtechnik GmbH ■ Munich ■ www.pcs.com ■ intus@pcs.com

Technical specifications subject to change without notice.



	CONVISION CC-7130	CONVISION CC-7200	CONVISION CC-7500
Description	Fixed 1.2 megapixel camera with CS-mount and multistreaming.	Fixed HDTV camera with 10x motor zoom, 2 megapixel and multistreaming.	HDTV PTZ dome camera with 10x motor zoom, 2 megapixel and multistreaming
Camera			
Picture sensor	1/3" Sony CCD	1/2,5" Sony CMOS	1/3" Sony CMOS
Lens	---	4.5 - 45mm F/1.8-2.2	5.1 - 51mm F/1.8-2.1
Angle of view	---	66° - 7°	50° - 5°
Min. illumination (b/w / color)	0.2 / 0.01 Lux at F=1.2	1 Lux at F=1.8	12 / 1 Lux at F=1.8
IR-LEDs for optimized night operation	no	no	no
Day/night with IR cut filter	yes	no	yes
Pan / Tilt / Zoom (PTZ)	no	- / - / 10x	360° / 90° / 10x
On screen display OSD	no	no	no
Video / Audio			
Video compression	H.264 (multistreaming)	H.264 (multistreaming)	H.264 (multistreaming)
Pixels	1280 x 960	1920 x 1080 (HDTV, 1080p)	1920 x 1080 (HDTV, 1080i)
White balance	manual, automatically	manual, automatically	manual, automatically
Privacy zones	4	4	16
Noise reduction (DNR)	yes	yes	no
Wide dynamic range (WDR)	no	no	yes
Sense Up	yes	yes	yes
Motion detection	yes (414 zones)	yes (414 zones)	yes (414 zones)
Audio input/output	2 way (Line in / Line out)	2 way (Line in / Line out)	2 way (Line in / Line out)
General			
Outdoor use	no	no	yes
Degree of protection/Operating temperature	IP50 / -10 to +50 °C	IP50 / -10 to +50 °C	IP67 / -30 to +60 °C
Additional features			vandalism protected
Power consumption	12 V DC / 500 mA or PoE	12 V DC / 500 mA or PoE	12 V DC / 3.0 A
Dimensions (HxWxD)	65 x 64 x 117 mm	77 x 65 x 133 mm	260 x 185 x 273 mm
Weight	0.5 kg	0.5 kg	4.0 kg
Color of housing	silver	white	white