

INTUS 300ro

- + Compact housing
- + For indoor and outdoor applications
- + Low power consumption
- + Integrated antenna
- + RS 485 Interface
- + CE-konform



Technical data

INTUS 300ro

The INTUS 300ro is a contactless RFID reader. It can be connected to an INTUS ACM40 or INTUS ACM8e access control manager via an RS485 line. The proximity cards for the INTUS 300ro readers can be used for time & attendance with the INTUS 3105 terminals as well as with INTUS terminals equipped with a Hitag reader programmed to MIRO mode.



	INTUS 300ro
Technology	EM4002 / EM4102
Protocol	300ro
Frequency	125 kHz
Interface	RS485
Connected to	INTUS ACM40, INTUS ACM40 Akku, INTUS ACM8e
Reading-distance	up to 5 cm
Operation mode	read (Serialnumber)
Signals	3 LEDs (yellow, green, red), 1 beeper
Digital Inputs	No
Digital Outputs	No
Supply voltage	12V AC or DC ±10%
Power consumption	max. 3 W
Dimensions (W x H x D)	81 mm x 81 mm x 21 mm
Mounting	Prepared for flush mounting (Ø 60mm) or Surface mounting
Colour	light grey (similar to RAL7035)
Temperature range	- 25° C to + 50° C
Protection class	IP54



www.pcs.com

PCS Systemtechnik GmbH
 Pfälzer-Wald-Str.36
 81539 München
 Fon + 49 (89) 68004 - 550
 intus@pcs.com

Ruhrallee 311
 45136 Essen
 Fon + 49 (201) 89416 - 0

Hofzeile 24
 A-1190 Vienna
 Fon + 43 (1) 3670 - 302

Technical specifications subject to change without notice.

PCS, INTUS, DEXICON, INTUS LBus and „PCS. The terminal people“ are trademarks of PCS Systemtechnik GmbH.



All other brands and products names are trademarks or registered trademarks of the respective companies and organisations.