



INTUS 400Be/400RP/400Ba/400EL

Readers for door intercom systems

-
- Installation in door intercom systems
 - Compatible with Baudisch, Behnke, Elcom, Ritto
 - State-of-the-art RFID technology
 - Tamper contact
 - Indoor or outdoor installation
 - Stand-alone capability
-

Time for security.



INTUS access readers to integrate your access control directly with your door intercom system. The built-in readers are compatible with the products of leading manufacturers such as Baudisch, Behnke, Elcom and Ritto.

As multi-ISO readers, they support both the LEGIC and MIFARE RFID technologies. INTUS 400 readers are suitable for indoor and outdoor installation.

INTUS
400Be/
400RP/
400Ba/
400El



General characteristics

- RFID reader for flush mounting
- Connects to INTUS terminals and Access Control Managers
- Made in Germany
- Reading and writing functions

Housing

- Installation in Baudisch, Behnke, Elcom, Ritto door intercom systems

Configuration

- Optical signaling: LED (blue, green, red)
- Acoustic signaling: 1 buzzer
- Temperature range: -20°C to +60 °C
- Degree of protection: IP40
- Tamper contact
- Door control by DI/DOs in the ACM
- Optional DI / DO module

Technology

- Multi-ISO reader for combined reading methods
- RFID reading technologies: MIFARE® DESFire® EV1/EV2/EV3, MIFARE® Classic, LEGIC advant, LEGIC prime, HITAG 1
- Frequency: 13.56 MHz (LEGIC, MIFARE), 125 kHz (HITAG 1)

Connectivity

- Interface: RS485, 2-wire
- Protocol: LBus
- Voltage supply: 12V DC or 24V DC

Dimensions (HxWxD)

- 120 x 90 x 38 mm (INTUS 400Be)
- 100 x 100 x 38 mm (INTUS 400RP)
- 110 x 110 x 38 mm (INTUS 400Ba)
- 120 x 120 x 38 mm (INTUS 400El)



© 2023-03 PCS Systemtechnik GmbH

PCS, INTUS und DEXICON are registered trademarks of PCS Systemtechnik GmbH.

All other names of products and services are trademarks of the respective companies and organizations.

PCS Systemtechnik GmbH · Pfälzer-Wald-Str. 36 · 81539 Munich, Germany · Tel. +49 89 68004 – 0
Ruhrallee 311 · 45136 Essen, Germany · Tel. +49 201 89416 – 0
intus@pcs.com · www.pcs.com

