



INTUS 700S

Reader for Siedle Vario 611 door intercom systems

-
- Compatible with Siedle Vario 611 door intercom systems
 - State-of-the-art RFID technology
 - Matt glass front
 - IK09 impact resistance rating
 - Available in Siedle standard colors
 - Optional PIN keypad
-

Time for security.



The INTUS 700S RFID access reader designed for installation in the Siedle Vario 611 door intercom system looks particularly smart with its matt glass front that minimizes reflections. It's also very robust, with an impact resistance rating of IK09 for extra toughness.

As a multi-ISO reader, INTUS 700S is compatible with both the LEGIC and MIFARE RFID technologies. The model comes in a range of Siedle standard colors: white, silver-metallic, micaceous dark grey and anthracite grey.

INTUS 700S



General characteristics

- RFID reader for flush mounting
- Connects to INTUS terminals and Access Control Managers
- Made in Germany
- Reading and writing functions

Housing

- Installation in Siedle Vario 611 door intercom systems

Configuration

- Backlit capacitive numerical touch keypad (optional)
- Optical signaling: LED (blue, green, red)
- Acoustic signaling: 1 buzzer
- Temperature range: -25 °C to +60 °C
- Degree of protection: IP54
- Tamper contact
- Door control by DI/DOs in the ACM
- 2 DIs (to connect potential-free switches)
- DO module (optional)

Technology

- Multi-ISO reader for combined reading methods
- RFID reading technologies: MIFARE® DESFire® EV1/EV2/EV3, MIFARE® Classic, LEGIC advant, LEGIC prime, HITAG 1
- Frequency: 13.56 MHz (LEGIC, MIFARE)

Connectivity

- Interface: RS485, 2-wire
- Protocol: LBus
- Voltage supply: 12V DC or 24V DC

Dimensions (HxWxD)

- 100 x 100 x 31 mm



© 2023-03 PCS Systemtechnik GmbH

PCS, INTUS und DEXICON are registered trademarks of PCS Systemtechnik GmbH.

All other names of products and services are trademarks of the respective companies and organizations.

PCS Systemtechnik GmbH · Pfälzer-Wald-Str. 36 · 81539 Munich, Germany · Tel. +49 89 68004 – 0
Ruhrallee 311 · 45136 Essen, Germany · Tel. +49 201 89416 – 0
intus@pcs.com · www.pcs.com

