



INTUS FLEX WALL READER

Mechatronic access control


-
- Plastic housing
 - Seamless integration of online and offline access control
 - Compact housing for indoor or outdoor installation
 - Ideal for locations without network connection
 - Control of garage doors, rolling gates or barriers via relay
-

Time for security.

pcs

The INTUS Flex wall reader controls your door and gate drives by potential-free contact activation. The entire electronics incorporating the reading unit, evaluator, control unit and switching relay are housed in one compact unit. This makes the wall reader ideal for connecting remote access points. The weather-protected version is equipped with a housing that resists both low temperatures and splash water.

INTUS FLEX WALL READER



General characteristics

- Made in Germany
- Optical and acoustic signaling
- Housing: Plastic housing

Configuration

- Memory capacity for bookings up to 1.024
- Memory capacity for block list entries up to 64
- Degree of protection: IP67 (outdoor option)
- Temperature range: -20 °C to +65 °C
- Dimensions (HxWxD): 85 x 110 x 15 mm (indoor); 100 x 100 x 40 mm (outdoor)

Installation

- Installation: indoors and outdoors
- Wall mounting, surface mounting

Functionality

- Single opening with time restriction
- Permanent opening (switchover function or based on a time model)
- Daytime release

Technology

- OSS-enabled
- INTUS Flex Air: MIFARE® DESFire® EV1/EV2/EV3, MIFARE® Classic, LEGIC advant, LEGIC prime
- INTUS Flex OnCard: MIFARE® DESFire® EV1/EV2/EV3, LEGIC advant
- radio frequency: 2,4 GHz Bluetooth®
- Power supply: 8V DC or 40V DC, 8V AC or 24V AC
- Number of relays: 1 (optionally extendable to 3 relays)



© 2023-04 PCS Systemtechnik GmbH

PCS, INTUS und DEXICON are registered trademarks of PCS Systemtechnik GmbH.

All other names of products and services are trademarks of the respective companies and organizations.

PCS Systemtechnik GmbH · Pfälzer-Wald-Str. 36 · 81539 Munich, Germany · Tel. +49 89 68004 – 0
Ruhrallee 311 · 45136 Essen, Germany · Tel. +49 201 89416 – 0
intus@pcs.com · www.pcs.com

