



Multipurpose terminal for time & attendance

# INTUS 5540

- + T&A terminal with read/write function
- + Large color display with high resolution
- + User interface (skin) on choice
- + Robust membrane keyboard
- + Dust and water proof up to IP65, -25°C ... to +50°C

Time & attendance

Time management

Access Control



## Technical Data INTUS 5540

Make life easy for yourself. The INTUS 5540 is a true all-round terminal for time and attendance recording as well as access control. It features a large antiglare color display with an advanced user interface. Select a pre-defined skin to match your corporate design. The robust membrane keyboard can be safely controlled even when the user is wearing gloves. If required, the built-in speakers can play sound clips, read information out loud, and acknowledge user operations acoustically for intuitive control. Highly reliable engineering ensures a long service life for the INTUS 5540. The housing is waterproof up to IP65. And if the terminal needs to be repaired, the AutoClone functionality will save your configuration. This is sustainability in time and attendance recording.

*PCS. The terminal people.*



# 5540



## Technical Data

INTUS 5540

### Controls and displays

- ARM9 (G45) 400 MHz
- Memory size 2 MB, upgradable to max. 6 MB
- 4.3" color display (480 x 272 pixels)
- Membrane keyboard with 5 function keys, 2 scroll keys, numeric bloc
- MagicEye (blue, green, red), 2 LEDs (green, red)
- Piezo indicator, speaker as an option
- Ethernet (10/100 Mbit/s)
- Integrated RFID reader Mifare, Legic, Hitag
- Realtime clock, calendar with lithium battery
- Tamper contact, stable lock
- Power supply  
110 ... 230V/PoE/SELV 24V

### Software support

- Integrated security package:  
firewall, encryption, three-step password system, IEEE 802.1X (i.p.)
- TCP/IP (IPv4 and IPv6) with DCHP
- INTUS COM communication software for Windows
- TPI-tasc terminal standard software to parametrize the terminal
- Freely programmable in TCL
- INTUS RemoteConf configuration and testing software for INTUS 5200/5500/5600

### Environment, dimensions, weight

- Protection degree IP30/with sealing kit IP65
- Temperature range 0°C ... +50°C,  
as an option -25°C ... +50°C
- Dimensions (H x W x D) 310 x 168 x 49 mm
- Weight 2.6 kg

### CE compliant

Product design: ergon3, Munich

Technical specifications subject to change without notice.

PCS, INTUS, DEXICON, „The terminal people.“ and „INTUS. The terminal.“ are trademarks or registered trademarks of PCS Systemtechnik GmbH. All other brands and product names are trademarks or registered trademarks of the respective companies and organisations.



**pcs**

PCS Systemtechnik GmbH  
Pfaelzer-Wald-Str. 36  
81539 Munich  
Phone +49-89-68004-550  
intus@pcs.com

Ruhrallee 311  
45136 Essen  
Phone +49-201-89416-0

Hofzeile 24  
1190 Vienna  
Phone +43-1-3670-302

www.pcs.com

made in  
germany