

INTUS 700

- + For flush / surface mounting
- + Supports Legic and Mifare
- + Optionally with capacitive touch PIN keypad
- + Symbols and numbers backlit
- + Elegant with matt full-glass front



Technical Data

INTUS 700

The INTUS 700 is an RFID access reader with the Legic Chip SM4200M for surface and flush mounting. To minimize reflections, it has a matt glass surface.

It is available in Legic and Mifare reading technologies and can be connected to all INTUS ACM access control managers.

Technology

- Mifare classic
- Mifare DESFire EV1/EV2
- Legic prime
- Legic advant

PIN keypad

- Optionally with capacitive touch PIN keypad

Frequency

- 13.56MHz (Legic, Mifare)

Interface

- LBus (RS485)

Temperature range

- -25°C ... +60°C

Voltage supply

- 12V ... 24V DC (int. reverse voltage protection)

Power consumption

- Maximum: 2.5 VA
- Typically: 2.0 VA

Signaling elements

- 3 LEDs / RGB multicolor
- 1 speaker for acoustic signaling

Dimensions (H x W x D)

- 100 x 80 x 19 mm (flush mounting)
- 100 x 80 x 41 mm (surface mounting)

Mounting

- Flush and surface mounting

Degree of protection

- IP54 (with correct installation)



PCS Systemtechnik GmbH
Pfälzer-Wald-Str.36
81539 München
Fon +49-89-68004-550
intus@pcs.com

Ruhrallee 311
45136 Essen
Fon +49-201-89416-0

www.pcs.com



Technical specifications subject to change without notice.

PCS, INTUS, DEXICON, „The terminal people.“ and „INTUS. The terminal.“ are registered trademarks of PCS Systemtechnik GmbH. All other brands and products names are trademarks or registered trademarks of the respective companies and organisations.

