

INTUS 700slim

- + Surface mounting, compact design
- + Optionally resin sealed
- + For Legic and Mifare
- + BLE (Legic Connect)
- + Optionally with membrane keypad



Technical Data

INTUS 700slim

Der INTUS 700slim is an RFID access reader with the Legic chip SM6300M. The slim design of the INTUS 700slim makes it ideal for mounting on door frames, frames or other narrow areas.

It is available in Legic and Mifare reading technologies as well as BLE (with Legic Connect). INTUS 700slim can be connected to all INTUS ACM access control managers.



Technology

- Legic prime
- Legic advant
- Mifare classic
- Mifare DESFire EV1/EV2
- BLE (with Legic Connect)

PIN keypad

Optionally with backlit membrane keyboard

Frequency

- 13.56 MHz (Legic, Mifare)

Interface

- LBus (RS485)

Temperature range

- -25°C ... +60°C

Voltage supply

- 12V ... 24V DC (int. reverse voltage protection)

Power consumption

- Maximum: 2.5 VA
- Typically: 2.0 VA

Signaling elements

- 3 LEDs / RGB
- 1 speaker for acoustic signaling

Dimension (H x W x D)

- 131 x 33 x 16 mm

Mounting

- Surface mounting

Weight

- 80 g

Connection technology

- 4-pin screw plug-in clump
- Optionally resin sealed with pre-assembled cable

Degree of protection

- Standard: IP66
- Resin sealed: IP68



PCS Systemtechnik GmbH
Pfälzer-Wald-Str.36
81539 München
Fon +49-89-68004-550
intus@pcs.com

Ruhrallee 311
45136 Essen
Fon +49-201-89416-0

www.pcs.com



Technical specifications subject to change without notice.

PCS, INTUS, DEXICON, "The terminal people." and "INTUS. The terminal" are trademarks or registered trademarks of PCS Systemtechnik GmbH.

All other brands and products names are trademarks or registered trademarks of the respective companies and organisations.

