

# INTUS PegaSys E-Cylinder 3.1

- + Lock cylinder for Mifare and Legic
- + Battery lifetime: up to 200,000 bookings
- + Easy integration into your access control system via NetworkOnCard
- + Suitable for existent profile cylinder holes—no need of drilling holes
- + Suitable for fire protection doors
- + For indoor and outdoor use



## Technical Data

### INTUS PegaSys E-Cylinder 3.1

The INTUS PegaSys E-Cylinder 3.1 is ideal for securing any door quickly and conveniently. Installation is completed in no time at all, without the need to drill any mounting holes. There is no need to wire the door, and with NetworkOnCard you can still integrate the E-Cylinder 3.1 seamlessly into the online access control infrastructure. When booking at an INTUS terminal, access permissions are written to your employee badge or tag. You operate all doors with a single medium: Online terminals, online readers, offline door terminals and offline lock cylinders. Of course, all INTUS PegaSys lock cylinders are fully compatible with the INTUS PegaSys door locks.

The clean design and the small knob diameter ensure a harmonic appearance, even in architecturally demanding buildings. The INTUS PegaSys E-Cylinder 3.1 efficiently replaces mechanical keys and increases security. A lost card is no longer a tragedy, unlike a lost master key in conventional mechanical locking systems. A battery life of up to 200,000 activations enables long-term, reliable operation.

### Functions

- Single access with time restriction
- Permanent access (switching function)
- Day activation
- Special days
- Transponder types: Mifare classic / DESFire, Legic prime / advant
- Optical and acoustic signalling
- E-cylinder corresponds to DIN 18252, DIN EN 15684, EN 1303 for installation in Euro profile locks according to DIN 18251
- Suitable for fire doors
- Power supply: 2 CR2450 3V batteries
- Battery life: up to 200,000 operations at 20 °C
- Operating temperature: -25 °C ... +65 °C
- Installation type: interior, exterior
- Degree of protection: IP54 for indoor use, IP66 for outdoor use



PCS Systemtechnik GmbH  
Pfälzer-Wald-Str.36  
81539 München  
Fon +49-89-68004-550  
intus@pcs.com

Ruhrallee 311  
45136 Essen  
Fon +49-201-89416-0

www.pcs.com



Technical specifications subject to change without notice.

PCS, INTUS, DEXICON, "The terminal people." and "INTUS. The terminal." are registered trademarks of PCS Systemtechnik GmbH. All other brands and products names are trademarks or registered trademarks of the respective companies and organisations.

**BHE**

