



Product Service

# CERTIFICATE

No. Z1 018247 0056 Rev. 00

**Holder of Certificate:** PCS Systemtechnik GmbH  
Pfälzer-Wald-Str. 36  
81539 München  
GERMANY

**Certification Mark:**




**Product:** Information Technology Equipment

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

**Test report no.:** 028-713169738-000

**Valid until:** 2025-01-21

**Date,** 2020-01-28

  
( Ralph Fischer )

TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD  
ZERTIFIKAT • CERTIFICATE • 認證證書 • CERTIFICADO • CERTIFIKAT • CERTIFICATE

A4 / 07.17



Product Service

# CERTIFICATE

No. Z1 018247 0056 Rev. 00

**Model(s):** INTUS 5200-24/X YY (heater optional)  
INTUS 5200-PoE/X YY  
INTUS 5205-SNT/X YY  
INTUS 5205-PoE/X YY

**Note to Model variants:**

X can be G or F. G stands for glass front. F stands for membrane keyboard. YY can be "Hitag", "La", "DF", "oL" which stand for different RFID readers, which has only minimal power consume and is not safety relevant.

## Parameters:

Model: INTUS 5200-24/X YY without optional heater  
Rated voltage: 12-24 Vdc  
Rated current: 0.5-0.25 A  
Protection class: III

Model: INTUS 5200-24/X YY with optional heater  
Rated voltage: 22-24 Vdc  
Rated current: 1.0A  
Protection class: III

Model: INTUS 5205-SNT/X YY  
Rated voltage: 12-24 Vdc  
Rated current: 0.5 A  
Protection class: III

Model: INTUS 5200-PoE/X YY  
INTUS 5205-PoE/X YY  
Rated voltage: 48 Vdc  
Rated current: 0.2 A (IEEE802.3af PoE Class2)  
Protection class: III

**Tested according to:** EN 62368-1:2014/A11:2017

**Production Facility(ies):** 018247